File as: Dye-Lite Leak Detection Tracer Dye

TRACER PRODUCTS

MATERIAL SAFETY DATA SHEET

TP-3090

Effective: 08/20/03

Page 1

Supersedes: 10/02/01

Section 1. Identification of the Substance/Preparation and Company

PRODUCT NAME: TP-3090

DESCRIPTION: Fluorescent Dye for Gasoline Engine Oil Systems

USE: Leak Detection

EMERGENCY TELEPHONE #: 800-424-9300 (24 HOURS) CHEMTREC; Call collect outside continental U.S.: 703-527-3887.

PRODUCT INFORMATION: Spectronics Corporation, 956 Brush Hollow Road, Westbury, NY 11590, 800-641-1133.

For calls originating outside continental U.S.: 516-333-1254.

Section 2. Composition/Information on Ingredients

Common Name/Chemical Name	CAS Number	% W	PEL(mg/m ³)	TLV(mg/m ³)
Lubricant Oil	See Below	80-90	5*	5*
Fluorescent Dye	See Below	10-20	NA	NA

Lubricant Oil: The specific identity has been withheld as a trade secret. New Jersey Trade Secret Registry Number NJ EIN 80100312-5010P. Fluorescent Dye: The specific identity has been withheld as a trade secret. New Jersey Trade Secret Registry Number NJ EIN 80100312-5000P.

*Airborne Oil Mist Exposure Limits: Lubricant Oil

ACGIH TLV: 5 mg/m³, 8 hr

ACGIH STEL: 10 mg/m³

OSHA-PEL: 5 mg/m3, 8 hr

Section 3. Hazards Identification

EMERGENCY OVERVIEW: Combustible liquid and vapor. May cause eye and skin irritation. Do not inhale, can cause respiratory system irritation. Do not swallow, can cause digestive tract irritation, nausea, vomiting, diarrhea.

imary Routes of Exposure: Eye. Skin. Inhalation (breathing).

Lye Contact: Can cause slight to mild irritation. Skin Contact: Irritation can occur following prolonged or repeated contact. Inhalation (breathing): Can cause irritation to eyes, nose, and respiratory tract following prolonged exposure. Ingestion (swallowing): Irritation to the mouth, throat, and stomach. Additional Effects: Depending on the route, frequency, and duration of exposure, toxicity may effect in the following organs and/or systems: Eye. Aggravation of Existing Conditions: Exposure to this product is not expected to contribute to, worsen or aggravate any existing medical conditions.

Carcinogenicity:	ACGIH	IARC	NTP	OSHA
Lubricant Oil	No	No	No	No
Fluorescent Dye	No	No	No	No

HMIS HAZARD RATING: Health: 1, Fire: 2, Reactivity: 0.

Section 4. First-Aid Measures

Eye Contact: Flush eyes with water for 15 minutes. If irritation develops, consult a physician. Skin Contact: Wash affected area with soap and water. If irritation develops, consult a physician. Inhalation (breathing): Remove to fresh air. If symptoms develop, seek immediate medical attention. If not breathing, give artificial respiration. Ingestion (swallowing): Call a physician immediately. Induce vomiting only as directed by medical personnel.

Section 5. Fire-Fighting Measures

Flash Point: Greater than 188° F (87° C); Test Method: SETAFLASH Closed Cup; Explosive Limit: LEL(%): Not Determined; UEL(%): Not Determined; Autoignition Temperature: Not Determined. Hazardous Combustion and Decomposition Products: Smoke, soot, and toxic/irritating fumes (i.e., carbon dioxide, carbon monoxide, etc.). Oxides of nitrogen. Fire and Explosion Hazards: May liberate irritating or toxic vapors during combustion or decomposition. Extinguishing Media: Small Fires: Use dry chemical, carbon dioxide, halon, water, spray, or foam. Large Fires: Water spray, fog, or alcohol foam. Fire-Fighting Procedures/Equipment: Fire fighters and others who may be exposed to the products of combustion should be equipped with NIOSH-approved, positive-pressure, self-contained breathing apparatus (SCBA) and full protective clothing.

TRACER PRODUCTS

MATERIAL SAFETY DATA SHEET

TP-3090

Effective: 08/20/03

Page 2

Supersedes: 10/02/01

Section 6. Accidental Release Measures

Spill Containment and Recovery: Contain with absorbent material, such as clay, soil or any commercially available absorbent. Shovel reclaimed dye and absorbent into recovery or salvage drums for disposal: Dispose of according to applicable local, state and federal regulations.

Section 7. Handling and Storage

Storage Conditions: Store in a cool, dry, well-ventilated area away from heat, ignition sources, and direct sunlight. Always keep containers tightly closed. Special Warning: Hot organic chemical vapors or mists can suddenly and without warning combust when mixed with air. Ignition can occur at typical elevated temperature process conditions. Transfer: Containers should be supported and grounded before opening, dispensing, mixing, pouring, and emptying. Open with nonsparking tools. If container is warm, open bung slowly to release internal pressure. Personal Hygiene: Wash thoroughly after handling, especially before eating, drinking, smoking, or using restroom facilities. Empty Container Precautions: Do not reuse empty container for any purpose.

Section 8. Exposure Controls/Personal Protection

Engineering Controls/Ventilation: Maintain airborne concentrations below the established exposure limits (see PEL and TLV in section 2) by providing adequate ventilation. General (dilution) ventilation should be acceptable. Eye Protection: Wear safety goggles. An eye wash facility should be readily available. Skin Protection: Wear protective clothing and appropriate impervious gloves. Respiratory Protection: Avoid breathing vapor and/or mist. If occupational exposure limits are exceeded wear NIOSH/OSHA approved equipment. High airborne concentrations may necessitate the use of self-contained breathing apparatus (SCBA) or a supplied air respirator. Respiratory protection programs must be in compliance with 29 CFR 1910.134.

Section 9. Physical and Chemical Properties

Appearance: Dark brown; Odor: Light blend petroleum; Physical State: Liquid; Specific Gravity (Water=1): 0.9; Vapor Pressure 68° F (20° C): 0.01 mmHg @ 20° C; Vapor Density (Air=1): >5; Percent Volatile by Volume (%): 0; Evaporation Rate (Butyl Acetate=1): <0.01; Solubility in Water: Insoluble; pH: Not Applicable; Boiling Range: >212° F (100° C); Volatile Organic Compounds (VOC) Content: Not Determined. Note: The physical data presented above are typical values and should not be construed as a specification.

Section 10. Stability and Reactivity

Chemical Stability: Stable under normal conditions of storage and use; Conditions to Avoid: High temperatures. Source of ignition. Incompatibility with other Materials: Oxidizers and reducers; Hazardous Polymerization: Will not occur. Hazardous Decomposition Products: Combustion may produce carbon monoxide and other asphyxiants.

Section 11. Toxicological Information

***************************************		Lubricant Oil	Fluorescent Dye*
Oral LD ₅₀	Rat	> 5000 mg/kg	> 5000 mg/kg
Dermal LD ₅₀	Rabbit	> 2000 mg/kg	> 2000 mg/kg
Inhalation LC ₅₀	Rat	Not available	Not available
Eye Irritation	Rabbit	Slight irritation	Slight irritation
Skin Irritation	Rabbit	Slight irritation	Mild irritation

^{*}Fluorescent Dye: Negative results were obtained in the Ames test. Negative results were obtained in the micronucleus assay.

Section 12. Ecological Information

No data are available on this product.

Section 13. Disposal Considerations

Disposal: Dispose of in accordance with all local, state, and federal regulations. General Statements: Federal regulations may apply to empty container. State and/or local regulations may be different. Special Instructions: Be sure to contact the appropriate government environmental agencies if further idance is required.

TRACER PRODUCTS

MATERIAL SAFETY DATA SHEET

TP-3090

Effective: 08/20/03

Page 3

Supersedes: 10/02/01

Section 14. Transport Information

DOT Shipping Name: Not Regulated; DOT Label: Not Applicable; DOT Identification No.: Not Applicable; Nonregulated shipments by air under 49 CFR, IATA/ICAO AND IMO.

Section 15. Regulatory Information

U.S. Federal Regulatory Information:

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

SARA Title III Information:

Ozone-Depleting Chemicals: No regulated ingredients. Section 302-Extremely Hazardous Substances: No regulated ingredients. Section 302-Reportable Quantity: Not Applicable. Section 311/312-Hazard Categories: Fire Hazard: Yes; Sudden Release of Pressure Hazard: No; Reactivity Hazard: No; Immediate (Acute) Health Hazard: Yes; Delayed (Chronic) Health Hazard: No. Section 313-Toxic Chemicals: No regulated ingredients. TSCA: The chemical components of this product are contained on the Section 8(B) Chemical Substance Inventory List (40 CFR 710).

CERCLA: No regulated ingredients.

State Right-To-Know:

Pennsylvania - New Jersey R-T-K:

 NAME
 NJ EIN
 %W

 Lubricant Oil
 80100312-5010P
 80-90

 Fluorescent Dye
 80100312-5000P
 10-20

California - California Proposition 65: No regulated ingredients.

CONEG: None.

Canada: This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

Class B Division 3 Class D Division 2 Subdivision B

CEPA - NPRI - No regulated ingredients.

Section 16. Other Information

USER'S RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions (in addition to those described herein) are required. Any health hazard and safety information contained herein should be passed on to your customers or employees, as the case may be. DISCLAIMER OF LIABILITY: The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the responsibility of the users to comply with all applicable federal, state and local laws and regulations.

NA = Not Available

End of Material Safety Data Sheet