

* Hazardous only as dust when product is sanded.
3 Sect. 313 of the Emergency Planning & Community Right-To-Know Act of 1986
and of 40 CFR 37
n New Jersey Label Law hazardous chemical

This product may contain small amounts of materials known to the
State of California to cause cancer and reproductive harm.

=====
===
SECTION III - PHYSICAL DATA
=====

BOILING RANGE: 318 to 401 F VAPOR DENSITY: HEAVIER THAN AIR
WEIGHT PER GAL: 7.2 - 7.3

EVAPORATION RATE: SLOWER THAN ETHER % VOLATILE VOLUME: 68.4 - 69.5

=====
===
SECTION IV - FIRE AND EXPLOSION HAZARD DATA
=====

D.O.T. FLAMMABILITY CLASSIFICATION: COMBUSTIBLE FLASH PT.: 110 F
PMC

LEL: 1.0%

EXTINGUISHING MEDIA: FOAM CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed
to
extreme heat or fire. Toxic gases may form when product burns.

SPECIAL FIREFIGHTING PROCEDURES: Do not use water stream on burning liquid.
Cool exposed containers with water. Use self-contained breathing apparatus.

=====
===
SECTION V - HEALTH HAZARD DATA
=====

EFFECTS OF OVEREXPOSURE - ACUTE:
Inhalation - Harmful if inhaled. May affect the brain or nervous system,
causing dizziness, headache or nausea.
Contact - Causes eye irritation.
Contact - Causes skin irritation.

Skin Absorption - Hazardous ingredients contained in this product have the
capacity to be absorbed through the skin in sufficient quantities to cause
systemic toxicity. See Safe Handling and Use Information (Section VIII).
Ingestion - Irritation of the digestive tract and nervous system depression
(drowsiness, dizziness, loss of coordination and fatigue). Aspiration Hazard
-

This material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

EFFECTS OF OVEREXPOSURE - CHRONIC:

Notice: Contains chemicals which may cause liver, kidney, thyroid and blood disorder upon overexposure, based on animal data.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

None expected when used in accordance with Safe Handling and Use Information (Section VIII).

PRIMARY ROUTE(S) OF ENTRY: DERMAL INHALATION INGESTION

EMERGENCY AND FIRST AID PROCEDURES: Inhalation - Remove from hazard area, maintain breathing, call physician. Skin Contact - Remove with soap and water. Eye Contact - Flush immediately with large amounts of water. Call physician. Ingestion - Drink 1 or 2 glasses of water to dilute. Do NOT induce vomiting. Call physician.

=====
===

SECTION VI - REACTIVITY DATA

=====
===

STABILITY: STABLE HAZARDOUS POLYMERIZATION WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Burning may produce carbon dioxide and carbon monoxide.

CONDITIONS TO AVOID: Elevated temperatures and build up of vapors.

INCOMPATIBILITY (MATERIALS TO AVOID): None reasonably foreseeable.

=====
===

SECTION VII - SPILL OR LEAK PROCEDURES

=====
===

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Avoid breathing vapors. Use non-sparking tools to return materials to container. Absorb residue with Fuller's earth.

WASTE DISPOSAL METHOD: Conventional procedures in compliance with local, state and federal regulations. Do not incinerate sealed containers.

=====
===

SECTION VIII - SAFE HANDLING AND USE INFORMATION

=====
===

RESPIRATORY PROTECTION:

Wear a properly fitted vapor/particulate approved by NIOSH/MSHA for use with paints (TC-23C) during application or sanding and until all vapors and spray mist are exhausted. In confined spaces or in situations where continuous spray operations are typical, or if proper respirator fit is not possible, wear

a positive-pressure, supplied air respirator (NIOSH/MSHA TC-19C)
VENTILATION: Adequate to maintain working atmosphere below T.L.V. and L.E.L.
(See Sect. II for ingredient data and concentrations). Mechanical exhaust
may

be required in confined areas. Discharge exhaust only in area away from
ignition sources.

PROTECTIVE GLOVES: Solvent impermeable gloves are required

EYE PROTECTION: Splash goggles or safety glasses with side shields.

OTHER PROTECTIVE EQUIPMENT: Clothing adequate to protect skin.

HYGIENIC PRACTICES: Remove and wash clothing before reuse. Wash hands
before
eating, smoking or using the washroom.

=====
===

SECTION IX - SPECIAL PRECAUTIONS

=====
===

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Combustible - Keep away from heat and flame.

OTHER PRECAUTIONS: Use only with adequate ventilation. Avoid prolonged
contact with skin and breathing of vapor spray mist or sanding dust. Close
container after each use. Keep out of reach of children. Do not take
internally.

=====
===

SECTION XX

=====
===

Hmis (Hazardous Materials Identification System) (R) NPCA

HMIS is a recognized workplace Hazard Communications System as required by
OSHA
(40CFR 1910. 1200). Information on establishing a complaint hazardous
communication program using HMIS is available from:

American Labelmark Co., Inc., Labelmaster Division
6724 N. Pulaski Rd., Chicago, IL 60646
1-800-621-5808

The ratings assigned by Benjamin Moore & Co. are only suggested ratings; the
contractor/employer has ultimate responsibility for HMIS rating where this
system is used.

PERSONAL PROTECTION: This code is left blank on Benjamin Moore & Co. MSDS's
as

it depends on application technique and the workplace ventilation. Please
read

Sections II through IX of this MSDS before deciding on appropriate protective
equipment and beginning work. There are codes available for this section
which

can be obtained from Labelmaster.

This product contains at least one toxic chemical listed in Section II that
is

subject to the reporting requirements of section 313 of the Emergency
Planning
and Community Right-to-Know Act of 1986 and 40 CFR 372.