

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name WEBCOL/CURITY Alcohol Prep Pads
Use/Size Wound Cleaner
Product Numbers 5033, 5110, 5150, 5750, 6818
Manufacturer/Supplier Tyco Healthcare/ Kendall
Address 15 Hampshire Street
Mansfield, MA 02048
Phone Number (508) 261-8000 (Monday – Friday 8:00 am to 5:00 pm)
Chemtrec Number (800) 424-9300
Revision Date: January 30, 2004
MSDS Date: September 14, 1999

This MSDS has been compiled in accordance with - EC Directive 91/155/EC - OSHA's Hazcom Standard (29 CFR 1910.1200)

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Component Name	CAS#/Codes	Concentration	R Phrases	Classification
Isopropyl alcohol	67-63-0 200-746-9	>60%	R11, R36, R67	F, Xi

3. HAZARD IDENTIFICATION

EU Main Hazards

Highly flammable.

Irritating to eyes.

Vapors may cause drowsiness and dizziness

Routes of Entry

- Absorption - Eye contact - Ingestion - Inhalation - Skin contact

Carcinogenic Status

Not considered carcinogenic by NTP, IARC, and OSHA.

Target Organs

- Central Nervous System - Skin - Eye - Liver – Respiratory System

Health Effects - Eyes

Liquid, mist or vapor will cause conjunctival irritation and possibly corneal damage.

Health Effects - Skin

Repeated or prolonged contact may produce defatting of the skin leading to irritation and dermatitis. Liquid may be absorbed through the skin but not in toxicologically significant amounts, unless the area of contact is large and exposure prolonged.

Health Effects - Ingestion

Swallowing may have the following effects:

- irritation of mouth, throat and digestive tract - central nervous system depression

A large dose may have the following effects:

- dizziness - drowsiness - headache - mental confusion - nerve damage leading to numbness and muscle weakness - fall of blood pressure - liver damage - lung damage

Health Effects - Inhalation

Exposure to vapor may have the following effects:

3. HAZARD IDENTIFICATION

- irritation of nose, throat and respiratory tract - central nervous system depression
Exposure to vapor at high concentrations may have the following effects:
- dizziness - drowsiness - headache - mental confusion - lung damage - fall of blood pressure -
liver damage - nerve damage leading to numbness and muscle weakness

4. FIRST AID MEASURES

Eyes:

Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.

Skin

Immediately flood the skin with large quantities of water, preferably under a shower. Remove contaminated clothing and continue washing. Contaminated clothing should be washed or dry-cleaned before re-use. Obtain medical attention if blistering occurs or redness persists.

Ingestion

Do not induce vomiting. Have victim drink 1-3 glasses of water to dilute stomach contents. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

Inhalation

Remove from exposure. If there is difficulty in breathing, give oxygen. Obtain medical attention immediately.

Advice to Physicians

Monitor for systemic secondary effects on liver and kidney; support and treat.

5. FIRE FIGHTING MEASURES

Extinguishing Media

Use foam, dry chemical or carbon dioxide. Be aware of the possibility of re-ignition. Keep containers and surroundings cool with water spray.

Unusual Fire and Explosion Hazards

Vapors can travel a considerable distance to a source of ignition and flashback. Flashback can occur if air temperature exceeds flash point. Be aware of possibility of re-ignition.

Protective Equipment for Fire-Fighting

Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal. Wear appropriate protective clothing. Eliminate all sources of ignition. Vapors can accumulate in low areas. Consider need for evacuation. Prevent the material from entering drains or water courses. Notify authorities if spill has entered water course or sewer or has contaminated soil or vegetation.

7. HANDLING AND STORAGE

Use in well ventilated area. Use local exhaust ventilation. Avoid inhaling vapor. Avoid contact with

7. HANDLING AND STORAGE

eyes, skin and clothing. Keep container tightly closed when not in use. Store away from sources of heat or ignition. Storage area should be: - cool - dry - well ventilated - away from incompatible materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

Exposure Limits are listed below, if they exist.

Isopropyl alcohol

UK EH40: OES 400ppm (980mg/m³) 8h TWA.

UK EH40: OES 500ppm (1225mg/m³) 15min TWA.

ACGIH: TLV 200ppm (980mg/m³) 8h TWA.

ACGIH: STEL 400ppm (1225mg/m³) 15min TWA.

OSHA: PEL 400ppm (980mg/m³) 8h TWA.

Can be absorbed through skin.

Engineering Control Measures

Good general room ventilation is expected to be adequate to control airborne levels.

Respiratory Protection

Respiratory protection if there is a risk of exposure to high vapor concentrations. The specific respirator selected must be based on the airborne concentration found in the workplace and must not exceed the working limits of the respirator.

Hand Protection

Chemical resistant gloves

For isopropyl alcohol, gloves made of polyvinyl alcohol do not provide adequate protection.

Eye Protection

Chemical goggles or safety glasses with side shields

Body Protection

If there is danger of splashing, wear: - overall or apron

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Non-woven cloth saturated with liquid
Color	Clear
Odor	Alcoholic
pH	No data.
Specific Gravity	0.8405
Boiling Range/Point (°C/F)	80 / 176
Melting Point (°C/F)	No data.
Flash Point (PMCC) (°C/F)	20 / 68
Vapor Pressure	No data.
Density	No data.
Solubility in Water	Miscible
Vapor Density (Air = 1)	2.1
Viscosity (cSt)	2.9 cps at <@2> °C

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to Avoid

- Heat - High temperatures - Static discharge - Exposure to direct sunlight - Mechanical shock

Materials to Avoid

- Strong oxidizing agents - Acids - Halogens - Aluminum - Acid anhydrides - Isopropyl alcohol may attack some forms of plastic, rubber and coatings

Hazardous Polymerization

Will not occur.

Hazardous Decomposition Products

- oxides of carbon

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Low order of acute toxicity predicted. Material may be harmful by skin absorption.

Isopropyl Alcohol: Oral LD50 (rat) 5045 mg/kg. Dermal LD50 (rabbit) 12800mg/kg. Inhalation LCLO (rat) 1600ppm 4h

Chronic Toxicity/Carcinogenicity

This product is not expected to cause long term adverse health effects.

(Isopropyl Alcohol) IARC assessment: this product is not classifiable as to its carcinogenicity to humans (Group 3). Chronic/Subchronic studies resulted in adverse effects to: - liver - spleen - biochemical effects - brain tissue degeneration - changes in reflex behavior - sensory nerve damage

Genotoxicity

This product is not expected to cause any mutagenic effects.

Reproductive/Developmental Toxicity

This product is not expected to cause reproductive or developmental health effects.

(Isopropyl Alcohol) Experimental studies in animals have provided some evidence of embryo/fetotoxicity and birth defects only at doses producing marked maternal toxicity.

12. ECOLOGICAL INFORMATION

Mobility

(Isopropyl Alcohol)

If released to soil, isopropyl alcohol is expected to have very high mobility.

Persistence/Degradability

(Isopropyl Alcohol)

Isopropyl alcohol is readily degraded in aerobic aqueous systems.

Bio-accumulation

(Isopropyl Alcohol)

An estimated BCF of 3 suggests the potential for bioconcentration in aquatic organisms is low.

Ecotoxicity

(Isopropyl Alcohol)

Tests on the following species gave a 96h LC50 of 1150mg/litre: - brown shrimp

Tests on the following species gave a 96h LC50 of 6.12-9.64mg/litre: - fathead minnows

13. DISPOSAL

Dispose of in accordance with all applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Do not cut, puncture or weld on or near to the container. Do not incinerate closed containers. Empty containers may contain hazardous residues. Dispose of containers with care.

14. TRANSPORT INFORMATION

DOT CFR 172.101 Data	Not Regulated per 49 CFR 173.4 Small Quantity Exemption
Proper Shipping Name	None
Class	None
UN Number	None
Packing Group	None
Classification for AIR Transport(IATA):	Consult current IATA Regulations prior to shipping by air.

15. REGULATORY INFORMATION

EU Label Information

Classification and labelling have been performed according to EU directives 67/548/EEC and 99/45/EC including amendments.

EU Hazard Symbol and Indication of Danger

F - Highly flammable

Xi - Irritant

R phrases

R11 - Highly flammable.

R36 - Irritating to eyes.

R67 - Vapours may cause drowsiness and dizziness.

S phrases

S2 - Keep out of reach of children.

S7 - Keep container tightly closed.

S16 - Keep away from sources of ignition - No smoking.

S24/25 - Avoid contact with skin and eyes.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

US REGULATIONS(Federal, State) and INTERNATIONAL CHEMICAL REGISTRATION LAWS**TSCA Listing**

This product contains ingredients that are listed on or exempt from listing on the EPA Toxic Substance Control Act Chemical Inventory.

EINECS Listing

All ingredients in this product are listed on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are exempt from listing.

DSL (Canadian) Listing

All ingredients in this product are listed on the Domestic Substance List (DSL).

MA Right To Know Law

All components have been checked for inclusion on the Massachusetts Substance List (MSL). Those

15. REGULATORY INFORMATION

components present at or above the de minimus concentration include: - Isopropyl Alcohol

PA Right To Know Law

This product contains the following chemicals found on the Pennsylvania Hazardous Substance List:
- Isopropyl Alcohol

NJ Right To Know Law

This product contains the following chemicals found on the NJ Right To Know Hazardous Substance List: - Isopropyl Alcohol

California Proposition 65

This product does not contain materials which the State of California has found to cause cancer, birth defects or other reproductive harm.

SARA Title III Sect. 302 (EHS)

This product does not contain any chemicals subject to SARA Title III Section 302.

SARA Title III Sect. 304

This product does not contain any chemicals subject to SARA Title III Section 304.

SARA Title III Sect. 311/312 Categorization

Immediate (Acute) Health Hazard
Delayed (Chronic) Health Hazard
Flammable

SARA Title III Sect. 313

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

16. OTHER INFORMATION

NFPA Ratings

NFPA Code for Flammability - 3
NFPA Code for Health - 1
NFPA Code for Reactivity - 0
NFPA Code for Special Hazards - None

HMIS Ratings

HMIS Code for Flammability - 3
HMIS Code for Health - 1
HMIS Code for Reactivity - 0
HMIS Code for Personal Protection - See Section 8

Abbreviations

N/A: Denotes no applicable information found or available
CAS#: Chemical Abstracts Service Number
ACGIH: American Conference of Governmental Industrial Hygienists
OSHA: Occupational Safety and Health Administration
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
STEL: Short Term Exposure Limit
NTP: National Toxicology Program
IARC: International Agency for Research on Cancer
EU: European Union
R: Risk
S: Safety

Prepared By: EnviroNet LLC.

15. REGULATORY INFORMATION

The information and recommendations presented in this MSDS are based on sources believed to be accurate; therefore, The Kendall Company assumes no liability for the accuracy or completeness of this information. It is the user's responsibility to determine the suitability of the information for their particular purposes.

JOHNSON MANUFACTURING COMPANY

Material Safety Data Sheet

to comply with 29 CFR 1910.1200,
OSHA's Hazard Communication Standard

Tin/Lead/Bismuth/Indium Alloys

Chip Quik, Inc Part #'s SMD1, SMD4.5, SMD8, SMD16, SMD32,

and all leaded Solder Spools

Section I:

Johnson Manufacturing Company
114 Lost Grove Road
Princeton IA 52768

Emergency Telephone 1-(563)-289-5123
CHEMTREC after hours 1-(800)-424-9300
Revised 1/1/2009

Section II: Hazardous Ingredients/Identity information

Hazardous Component	CAS #	OSHA TWA	ACGIH TWA	Other limits	
Tin	7440-31-5	2mg/M3	2mg/M3	NE	<u>807</u> 12%
* + Lead	7439-92-1	0.05mg/M3	0.05mg/M3	NE	18
Bismuth	7440-69-9	NE	NE	NE	49
Indium	7440-74-6	0.1mg/M3	0.1mg/M3	NE	21

Only those ingredients listed in this section have been determined to be hazardous as defined in 29CFR 1910.1200.
An ingredient marked with an asterisk(*) is also listed in 29CFR 1910.1200(D) #4 as a known or suspected cancer hazard.

+ denotes a chemical regulated as toxic by the Environmental Protection Agency (EPA) as outlined in 40CFR Part 372 (section 313)

Section III: Physical/Chemical Characteristics

Boiling Point: 2840 F
Vapor Pressure (mm Hg): 760 @ 3164F
Vapor Density: NE
Solubility in water: insoluble
Appearance and odor: silver grey solid, odorless

Specific Gravity: 9.0
Melting Point: 291 F
Evaporation Rate
(butyl acetate=1): < 1

Section IV: Fire and Explosion Hazard Data

Flash Point: non flammable
Extinguishing media: all
Special fire fighting procedures: use self-contained breathing apparatus
Unusual Fire and Explosion Hazards: May release toxic metal & oxide fumes. High concentrations of dust may present explosion hazard. Water trapped below molten metal may explode thus spattering molten metal.

Flammable limits lel: NA uel: NA

Section V: Reactivity Data

Stability : STABLE Conditions to avoid : none
Incompatibility (materials to avoid): oxidizing materials, turpentine, acids, chlorides.
Hazardous Decomposition or Byproducts (incomplete combustion): toxic metal & metal oxide fumes
Hazardous Polymerization: WILL NOT OCCUR Conditions to avoid: none

Section VI: Health Hazard Data

Routes of entry: Inhalation? yes Skin? no Ingestion? Yes

Health Hazards (acute and chronic): Contact with dust & fumes may cause skin, eye and respiratory irritation. Ingestion and/or inhalation of material or fumes may result in "metal fume fever", flu like symptoms, insomnia, muscle weakness, nausea and abdominal pain. Gross inhalation or ingestion may be toxic and can result in death. Symptoms of toxicity may take hours or days to manifest. Chronic exposures, inhalation or ingestion, may result in kidney, red blood cell, reproductive & nervous system effects. Health effects may be cumulative over many exposures. Studies show that health risks vary by individual. Minimize exposure as a precaution. See OSHA 29CFR 1910.1025(subpart Z) for more information.

Carcinogenicity: not determined NTP? no IARC Monographs? Lead-suspect

Signs and symptoms of exposure: Inhalation-Nose & throat irritation, headache, dizziness, difficulty breathing, coughing, flu like symptoms, metallic taste in mouth. Ingestion-nausea, vomiting, cramps. Skin-redness, burning, rash. Eye-redness, tearing, blurred vision.

Medical Conditions Aggravated by exposure: Blood, kidney, reproductive & nervous system conditions

Emergency first aid procedures:

Skin: Flush with water immediately - Seek medical attention if burns are present.

Eyes: Flush with water for 15 minutes - Seek medical attention

Ingestion: Drink large amounts of water, induce vomiting if practical- seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Support respiration if required - Seek medical attention.

Section VII: Precautions for Safe Handling and Use

Steps to be taken if material is released or spilled: Vacuum, absorb or flush in to a chemical sewer. Do not use any method which will generate dust.

Waste Disposal Method: dispose of in accordance with all local state and federal regulations

Other Precautions: Avoid skin & eye contact, inhalation & ingestion of material or fumes. Wash thoroughly after use. Wash contaminated clothing before reuse. Avoid eating or smoking in lead use area. Keep away from children.

Section VIII: Control Measures

Respiratory Protection (type): Dust mask for particulates. Metal fume/HEPA respirator for fumes.

Ventilation Local Exhaust preferred Special: HEPA filters required

 Mechanical: OK Other: NE

Protective Gloves: impervious Eye Protection: Goggles or face shield

Other Protective Clothing or Equipment: as required to avoid contact.

Work/Hygienic Practices: Wash after use. Follow good industrial hygienic practices.

Section IX: Additional Information

DOT/IATA Hazard Classification: This product is not listed as a DOT or IATA hazardous material.

NFPA Classification (NFPA 325M, 8th edition)(Health, Flammability, Reactivity): 2-0-0 This product contains components known to the state of California to cause cancer or reproductive harm.

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to JOHNSON MANUFACTURING at the time of issue. No warranty, guarantee, or representation is made by JOHNSON MANUFACTURING nor does JOHNSON MANUFACTURING assume

any responsibility in connection therewithin; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. NE = not established NA = not applicable

SMT International, LLC
MATERIAL SAFETY DATA SHEET (MSDS)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION *Manufactured for Chip Quik, Inc.*

PRODUCT NAME: Amtech Tacky Paste Flux, Series #61 Flux, 200, 400, 500, 4000, SynTECH, WSFC-305L
SYNONYMS: Tacky Flux / **Chip Quik Part #'s SMD291, SMD291ST2CC6, SMD291ST8CC**

MANUFACTURER: SMT International, LLC
ADDRESS: PO Box 989 Deep River, CT 06417 USA
PHONE: 860-526-8300
FAX: 860-526-8243
EMERGENCY: Infotrac-(800)535-5035

CHEMICAL NAME: N/A
CHEMICAL FAMILY: Mixture
CHEMICAL FORMULA: N/A

REVISION DATE: December 17, 2010
DOCUMENT NAME: MSDS-Tacky Flux-008

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Exposure Limits
Modified Rosins	N/A	N/A
Pine Oil Derivatives	8000-41-7	N/A
Proprietary Ingredients	N/A	N/A
Mixed Carboxylic Acids	N/A	N/A

SECTION 2 NOTES:
Percentages of individual components are not listed as this information is considered a trade secret.

SECTION 3: HAZARDS IDENTIFICATION

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact

EYE CONTACT: May cause moderate irritation. Do not allow material to come in contact with eyes.

SKIN CONTACT: May cause moderate skin irritation.

INHALATION: Moderately toxic. May cause irritation to the respiratory tract.

INGESTION: Harmful if swallowed. May cause irritation to the mouth, throat, and stomach. May cause abdominal discomfort, nausea, vomiting, and/or diarrhea.

CHRONIC: Not established.

CARCINOGENICITY:

OSHA: N/A **ACGIH:** N/A **NTP:** N/A **IARC:** N/A

SECTION 3 NOTES:

SMT International, LLC does not recommend, manufacture, market, or endorse any of its products for human consumption.

SECTION 4: FIRST AID MEASURES

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Call a physician or Poison Control Center immediately. Do not induce vomiting.

INHALATION: Remove to fresh air. If not breathing, seek immediate medical attention.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR: Not established
FLASH POINT: Not established
AUTOIGNITION TEMPERATURE: N/A
EXTINGUISHING MEDIA: Dry chemical, foam

SPECIAL FIRE FIGHTING PROCEDURES: Do not use water. Use NIOSH-approved self-contained Breathing Apparatus and full protective clothing if involved in a fire.

UNUSUAL FIRE AND EXPLOSION HAZARDS: This product does not present any unusual fire and explosion hazards.

HAZARDOUS DECOMPOSITION PRODUCTS: Not established

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: If material spills or leaks, collect and place into a properly labeled waste container. Remove traces of tacky flux using cloth rags or paper towels moistened with Isopropyl Alcohol. Follow on-site personal protective equipment recommendations.

SECTION 6 NOTES:

See Sections 3, 4, and 7 for additional information.

SECTION 7: HANDLING AND STORAGE

HANDLING/STORAGE: Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes or dust. Avoid contact with eyes, skin, and clothing.

OTHER PRECAUTIONS: Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

SECTION 7 NOTES:

For industrial use only.
Keep out of reach of children.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

RESPIRATORY PROTECTION: Use with adequate ventilation.

EYE PROTECTION: Use with appropriate safety glasses.

SKIN PROTECTION: Protective gloves and clothing should be worn when handling material. Wash hands thoroughly with soap and water upon leaving the work area.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Clear, White, or Yellow to Dark Amber gel
ODOR:	Mild odor
pH as SUPPLIED:	N/A
BOILING POINT:	Not established
MELTING POINT:	Not established
FREEZING POINT:	Not established
VAPOR PRESSURE (mmHg):	N/A (°F/°C)
VAPOR DENSITY (AIR = 1):	N/A (°F/°C)
SPECIFIC GRAVITY (H₂O = 1):	N/A
EVAPORATION RATE:	N/A
SOLUBILITY IN WATER:	Partially
PERCENT SOLIDS BY WEIGHT:	N/A
PERCENT VOLATILE:	N/A (°F/°C)
VOLATILE ORGANIC COMPOUNDS (VOC):	N/A (°F/°C)
MOLECULAR WEIGHT:	N/A
VISCOSITY:	N/A (°F/°C)

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	Stable
CONDITIONS TO AVOID (STABILITY):	Freezing temperatures. High temperatures.
INCOMPATIBILITY (MATERIAL TO AVOID):	Strong oxidizing materials
HAZARDOUS DECOMPOSITION/BY-PRODUCTS:	Harmful organic fumes and toxic oxide fumes may form at elevated temperatures.
HAZARDOUS POLYMERIZATION:	Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

CARCINOGENICITY: None known
IRRITANCY OF PRODUCT: Not established
SENSITIZATION TO PRODUCT: Not established
OTHER: Prolonged or repeated exposure to flux fumes may cause workers to develop occupational asthma.

SECTION 12: ECOLOGICAL INFORMATION

ENVIRONMENTAL: Not established

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Scrap and waste solder should be stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

SECTION 14: TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

US DOT Hazardous Material Classification:	Tacky Flux is not listed as a DOT hazardous material
Water Transportation:	Tacky Flux is not listed as a hazardous material
IATA Hazardous Material Classification:	Tacky Flux is not listed as IATA hazardous material

SECTION 15: REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:	Not regulated
STATE REGULATIONS:	Not regulated
INTERNATIONAL REGULATIONS:	Not regulated

SECTION 16: OTHER INFORMATION

HMIS Rating: Health=1 Flammability=1 Physical Hazard=0 Personal Protection=X

PREPARATION INFORMATION:
This update supersedes all previously released documents.

DISCLAIMER:
The information contained herein is based on data considered to be accurate and is offered at no charge. No warranty is expressed or implied regarding the accuracy of this data. Liability is expressly disclaimed for loss or injuring arising out of use of this information or the use of any materials designated herein.