
COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1AS-1110

SECTION 3 - HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Exposure to liquid may cause mild eye irritation. Symptoms may include stinging, tearing, and redness.

SKIN: May cause skin defatting with prolonged exposure. Exposure may cause skin irritation. Prolonged or repeated exposure may dry the skin.

INHALATION: Causes mild respiratory irritation. Breathing large amounts may be harmful. Symptoms of exposure may include irritation (nose, throat, respiratory tract) and CNS depression.

INGESTION: Swallowing small amounts of this product during normal handling is not likely to cause harmful effects, but swallowing large amounts may be harmful.

CHRONIC EFFECTS

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause respiratory and/or skin sensitization.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

POSSIBLE ROUTES OF ENTRY

Inhalation, ingestion, skin absorption.

CARCINOGENICITY

IARC lists cobalt and cobalt compounds as possible human carcinogens (Group 2B). However, there is inadequate evidence of the carcinogenicity of cobalt and cobalt compounds in humans.

ACGIH has given cobalt a rating of A3, animal carcinogen. They state that available epidemiological studies do not confirm an increased risk of cancer in exposed humans.

SECTION 4 - FIRST AID MEASURES

EMERGENCY FIRST AID:

EYE CONTACT

If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water, holding eyelids apart. If symptoms persist, seek medical attention.

SKIN CONTACT

Remove contaminated shoes and clothing, and flush affected area with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1AS-1110

an appropriate absorbent material. Prevent spilled material from entering sewers, storm drains, other authorized treatment drainage systems, and natural waterways. Stop spill/release if it can be done, and stay away from spill. Isolate danger and keep unauthorized personnel out. Use non-sparking tools and explosion-proof equipment.

CLEAN-UP

Warn occupants in surrounding and downwind areas of fire and explosion hazard to stay clear. Remove from surface with suitable absorbents. If allowed by local authorities, sinking and/or suitable dispersants may be used in non-confined waters.

SECTION 7 - HANDLING AND STORAGE

HANDLING

Keep container closed. Handle and open container with care. Open container slowly to relieve any pressure. Do NOT cut, weld or puncture on or near container.

STORAGE

Keep container(s) tightly closed. Use and store this product in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Keep away from any incompatible material. Protect container(s) against physical damage.

SPECIAL COMMENTS

WARNING: Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures and pressures, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources.

SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION

VENTILATION

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH for protection against chemicals in Sections (2 &/or 15).

EYE PROTECTION

Wear safety glasses or goggles to protect against exposure. Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other types of safety glasses.

PROTECTIVE GLOVES

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1AS-1110

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

Dispose of this product in accordance with applicable local, county, state and federal regulations, by incinerating, or treating and disposing in approved facility. Do not incinerate closed containers.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS : NOT REGULATED (In containers less than 119 gallons or 450 liters via surface transportation).
COMBUSTIBLE LIQUID (In containers of more than 119 gallons capacity) for surface shipments within the U.S. and Canada, and apply the DOT information, listed below:
DOT PACKAGING GROUP : PG III
DOT LABEL : NONE
DOT SHIPPING NAME : PAINT
DOT PLACARD : NONE
UN/NA NUMBER : UN1263

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATORY INFORMATION

TSCA SECTION 8(b) - INVENTORY STATUS:

All components of this product are either listed on the U.S. Toxic Substances Control Act (TSCA) inventory of chemicals or are otherwise compliant with TSCA Regulations.

SARA 313 TOXIC CHEMICALS:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

COBALT 2-ETHYLHEXANOATE

CAS# 136-52-7 PCT BY WT: .1150

SECTION 16 - OTHER INFORMATION

Prepared by :
Date of issue : 01/31/2011
Last Revision Date : 08/22/2007
MSDS Prepared for :

COMPLEMENTARY COATINGS CORP
MATERIAL SAFETY DATA SHEET

1AS-1110

MSDS Last Prepared : NONE
HMIS Rating: Health- 2* Flammability- 2
Reactivity- 0

This Material Safety Data Sheet conforms to the Hazard Communication Standard, 29 CFR 1910.1200(g)(4).

The above information pertains to this product as currently formulated and is based on the information available, as of this date. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.

Abbreviations used: int.- interior; ext.- exterior; MSDS - Material Safety Data Sheet; HMIS - Hazardous Materials Information System; CAS - Chemical Abstracts Services; pct - percent; wt - weight; mm Hg - millimeters of mercury; F - Fahrenheit; ACGIH - American Conference of Governmental Industrial Hygienists; TLV - Threshold Limit Value; OSHA - Occupational Safety and Health Administration; PEL - Permissible Exposure Limit; TWA - Time-Weighted Average; STEL- Short Term Exposure Limit; N/A- Not applicable IARC - International Agency for Research on Cancer; NE - Not established NTP - National Toxicological Program; CFR - Code of Federal Regulations; OSHA - Z 29CFR 1910, Subpart Z; VOC - Volatile Organic Compounds; TCC - Tag Closed Cup; LEL - Lower Explosive Limit; Mg/m³ or Mg/Cu M - milligram per cubic meter; mppcf - millions of particles per cubic foot; ppm - parts per million; NIOSH - National Institute of Occupational Safety and Health; MSHA - Mine Safety and Health Administration; CNS - Central Nervous System.