DUTCH BOY INC -- 3835, FRESH LOOK INTERIOR LATEX SEMI-GLOSS (S

==========

MSDS Safety Information

==========

FSC: 8010
MSDS Date: 06/21/1994
MSDS Num: BWYRP
LIIN: 00N056994
Product ID: 3835, FRESH LOOK INTERIOR LATEX SEMI-GLOSS (SUPDAT)
MFN: 01
Responsible Party
Cage: IO967
Name: DUTCH BOY INC
Address: 2325 HOLLINS FERRY RD
City: BALTIMORE MD 21230-3030
Info Phone Number: 216-566-2902
Emergency Phone Number: 216-566-2917
Published: Y

==========

Contractor Summary

==========

Cage: 59019
Name: DUTCH BOY
Box: 6709
City: CLEVELAND OH 44101
Phone: 216-566-2902
Cage: IO967
Name: DUTCH BOY INC
Address: 2325 HOLLINS FERRY RD
City: BALTIMORE MD 21230-3030
Phone: 216-566-2902

==========

Ingredients

==========

Cas: 112-34-5
RTECS #: KJ9100000
Name: ETHANOL, 2-(2-BUTOXYETHOXY)-; (2-(2-BUTOXYETHOXY)-ETHANOL). VP:0.06.
% Wt: 2
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)

Cas: 107-21-1
RTECS #: KW2975000
Name: ETHYLENE GLYCOL (SARA 313) (CERCLA). VP:0.12.
% Wt: 1
OSHA PEL: 50 PPM (MFR)
ACGIH TLV: 50 PPM, VAPOR, C
EPA Rpt Qty: 1 LB
DOT Rpt Qty: 1 LB

Cas: 13463-67-7
RTECS #: XR2275000
Name: TITANIUM OXIDE; (TITANIUM DIOXIDE)
% Wt: 17
OSHA PEL: 15 MG/M3 TDUST
ACGIH TLV: 10 MG/M3 TDUST

RTECS #: 9999999VO
Name: VOLATILE ORGANIC COMPOUNDS (THEORETICAL): 0.86 LB (103 GM).

Name: SUPP DATA:ARE LISTED, APPLIC LIMS FOR NUISANCE DUSTS ARE ACGIH TLV 10 MG/M3 TDUST, OSHA PEL 15 MG/M3 TDUST;5 MG/M3 RESP.

Name: RESP PROT:FOR DUST WHICH MAY BE GENERATED FROM THIS PRODUCT, UNDERLYING PAINT OR THE ABRASIVE.

Name: VENT:1910.94, 1910.107, 1910.108.

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: EXPOS MAY BE BY INHAL &/OR SKIN/EYE CONT, DEPENDING ON CNDTNS OF USE. TO MIN EXPOS, FOLLOW RECS FOR PROPER USE, VENT & PERSONAL PROT EQUIP. ACUTE:IRRIT OF EYES, SKIN & UPPER RESP SYS. IN CONFINED AREA VAPS IN HIGH CONCS MAY CAUSE HDCH, NAUS /DIZZ. REDNESS & ITCH/BURNING SENSATION MAY INDICATE EYE/ (EFTS OF OVEREXP)
Explanation Of Carcinogenicity: NOT RELEVANT
Signs And Symptions Of Overexposure: HLTH HAZ:EXCESSIVE SKIN EXPOS. CHRONIC:ETHYLENE GLYCOL IS CONSIDERED ANIMAL TERATOGEN. IT HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN RATS & MICE AT HIGH DOSES WHEN GIVEN IN DRINKING WATER/BY GAVAGE. PRLNG OVEREXP TO SOLV INGS MAY CAUSE ADVERS E EFTS TO LIVER & URINARY SYS. RATS EXPOS TO TITANIUM DIOXIDE DUST AT (SUPDAT)
Medical Cond Aggravated By Exposure: NONE GENERALLY RECOGNIZED.
First Aid: INHAL:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET. SKIN:WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE RE-USE. EYE:FLUSH W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. GET MEDIC AL ATTENTION. INGEST:GET MEDICAL ATTENTION.

Handling and Disposal

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Methods: WASTE FROM THIS PROD IS NOT HAZ AS DEFINED UNDER RCRA 40 CFR 261. INCIN IN APPROVED FACILITY. DO NOT INCINERATE CLSD CNTNR. DISPOSE OF I/A/W FED, STATE & LOCAL REGULATIONS REGARDING POLLUTION.
Handling And Storage Precautions: DOL STOR CATEGORY:3B. KEEP CNTNR CLSD WHEN NOT IN USE. TRANSFER ONLY TO APPRVD CNTNRS W/COMPLETE & APPROP LABELING. DO NOT TAKE INTERNALLY.
Other Precautions: KEEP OUT OF REACH OF CHILDREN. USE ONLY W/ADEQ VENT.AVOID BRTHG VAP & SPRAY MIST. AVOID CONT W/SKIN & EYES. THIS COATING MAYCONTAIN MATLS CLASSIFIED AS NUISANCE PARTICULATES WHICH MAY BE PRESENT ATHAZ LEVELS ONLY DURING SANDING/ (SUPDAT)

Fire and Explosion Hazard Information

Lower Limits: 0.9%
Upper Limits: 15.3%
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM.
Fire Fighting Procedures: USE NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP (FP N). WATER SPRAY MAY BE INEFT. IF WATER IS USED, FOG NOZZS ARE PREF. WATER MAY BE USED TO COOL CLSD (SUPDAT)
Unusual Fire/Explosion Hazard: CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

Control Measures

Respiratory Protection: IF PERSONAL EXPOS CANNOT BE CONTROLLED BELOW APPLIC LIMS BY VENT, WEAR PROPERLY FITTED NIOSH/MSHA APPRVD ORG VAP/PARTICULATE RESP FOR PROT AGAINST INGS. WHEN SANDING/ABRADING DRIED FILM, WEAR NIOSH/MSHA

APPRVD DUST/MIST FILTER RESP
Ventilation: LOC EXHST PREF. GEN EXHST ACCEPT IF EXPOS TO INGS IS MAINTAINED BELOW APPLIC EXPOS LIMS. REFER TO OSHA STDS
Protective Gloves: IMPERVIOUS GLOVES (FP N).
Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).
Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA (FP N).
Work Hygienic Practices: WASH HANDS AFTER USING.
Supplemental Safety and Health: MFR'S TRADE NAME/PART NO:FINISH, ULTRA HIDE WHITE. FIRE FIGHT PROC:CNTNRS TO PVNT PRESS BUILD-UP & POSS AUTOIGNIT/EXPLO WHEN EXPOS TO EXTREME HEAT. EFTS OF OVEREXP:250 MG/M3 DEVELOPED LUNG CANCER, HOWEVER, SUCH EXPOS LEVELS ARE NOT ATTAINAB LE IN WORKPLACE. OTHER PREC:ABRADING OF DRIED FILM. IF NO SPECIFIC DUSTS
==========
Physical/Chemical Properties
==========
B.P. Text: >212F,>100C
Vapor Pres: SEE INGS
Vapor Density: HVR/AIR
Spec Gravity: 1.18
PH: 9
Evaporation Rate & Reference: SLOWER THAN ETHER
Appearance and Odor: NONE SPECIFIED BY MANUFACTURER.
Percent Volatiles by Volume: 69
==========
Reactivity Data
==========
Stability Indicator: YES
Stability Condition To Avoid: NONE KNOWN.
Materials To Avoid: NONE KNOWN.
Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT
==========
Toxicological Information
==========
==========
Ecological Information
==========
==========
MSDS Transport Information
==========
==========
Regulatory Information
==========
==========
Other Information
==========
==========
HAZCOM Label
==========
Product ID: 3835, FRESH LOOK INTERIOR LATEX SEMI-GLOSS (SUPDAT)
Cage: IO967
Assigned IND: Y
Company Name: DUTCH BOY INC
Street: 2325 HOLLINS FERRY RD
City: BALTIMORE MD
Zipcode: 21230-3030
Health Emergency Phone: 216-566-2917
Label Required IND: Y
Date Of Label Review: 03/10/1995
Status Code: C
Label Date: 03/10/1995
Origination Code: G
Chronic Hazard IND: Y

Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Moderate
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: ACUTE:IRRITATION OF EYES, SKIN & UPPER RESPIRATORY SYSTEM. IN CONFINED AREA VAPORS IN HIGH CONCENTRATIONS MAY CAUSE HEADACHE, NAUSEA OR DIZZINESS. REDNESS & ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN CONTACT. CHRONIC:ET HYLENE GLYCOL IS CONSIDERED AN ANIMAL TERATOGEN. IT HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LAB ANIMALS. OVEREXPOSURE MAY ADVERSELY EFFECT LIVER & URINARY SYSTEM.

==========

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.