



Search



MSDS 250,000+

MSDS : MOLYKOTE 4X SPRAY
 CAS : 71-55-6
 NAME : methyl chloroform (1,1,1-trichloroethane) (sara iii)
 propellant (type not specified)

Catalog of Chemical Suppliers, Buyers, Custom Synthesis Companies And Equipment Manufacturers
 [MOLYKOTE 4X SPRAY 71-55-6]

Suppliers:

Not Available

Buyers:

Not Available

===== Product Identification =====

MSDS NAME:MOLYKOTE 4X SPRAY
 NIIN:00D000851
 MSDS Number: BBDLH
 === Responsible Party ===
 Company:DOW CORNING INC.
 Address:3901 SOUTH SAGINAW ROAD
 Box:997
 City:MIDLAND
 State:MI
 ZIP:48640
 Country:US
 Info Phone Num:517-496-5900
 Emergency Phone Num:517-496-5900
 CAGE:5D028
 === Contractor Identification ===
 Company:DOW CORNING CORP
 Address:3901 S SAGINAW RD
 Box:997
 City:MIDLAND
 State:MI
 ZIP:48686-0997
 Country:US
 Phone:517-496-6000/517-496-6315
 CAGE:5D028
 Company:DOW CORNING CORP
 Address:2200 W SALZBURG RD
 Box:City:AUBURN
 State:MI
 ZIP:48611
 Country:US
 Phone:517-496-4388
 CAGE:71984

===== Composition/Information on Ingredients =====

Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 80%.
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Name:PROPELLANT (TYPE NOT SPECIFIED)

=====
Hazards Identification
=====

Effects of Overexposure:EYES:MAY IRRITAT. SERIOUSLY W/MOD.CORNEAL INJURY; SKIN:SIGHT IRRITAT.-PRLNGD EXPOS; INHAL: IRRITAT.

=====
First Aid Measures
=====

Eyes: FLUSH W/WATER; SKIN:WIPE OFF & FLUSH W/WATER;
INHAL:REMOVE TO FRESH AIR. OBTAIN MEDICAL ATTENTION IMMEDIATELY;
ORAL: NO PROBLEM.

=====
Fire Fighting Measures
=====

Flash Point:N/R,AEROSOL CAN
Extinguishing Media:WATER, WATER FOG, CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WEAR SCBA' & PROTECTIVE CLOTHNG IN FIGHTING CHEMICAL FIRES.
Unusual Fire/Explosion Hazard:USE IN AN ENCLOSED AREA COULD RESULT IN A FLAMMABILITY HAZARD.

=====
Accidental Release Measures
=====

Spill Release Procedures:USE PROPER PROTECTIVE EQUIP.; USE ABSORBENT MATERIAL FOR OIL-LIKE RESIDUE. AVOID BREATHING VAPOR. VENTILATE ENCLOSED AREA./USE IMPERVIOUS PROTECTIVE CLOTHING. & RESPIRATORY PROTECTION UNLESS LOCAL EXH AUST VENTILATION IS ADEQUATE.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE BELOW 120F?49C. USE REASONABLE CARE & USE W/ADEQUATE VENTILATION. DONOT USE NEAR SPARKS,HEAT, OR OPEN FLAME, CONTAINS FLAMMABLE INGREDIENTS.
Other Precautions:USE SAFETY GLASSES AS A MINIMUM. WASH PRIOR TO EATING AND @ END OF WORK.SHIFT. USE RESPIRATORY PROTECTION UNLESS LOCAL EXHAUST IS ADEQUATE, OR AIR QUALITY IS BELOW TLV.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH APPRVD.RESPIR. DEVICES FOR ORGANIC VAPOR/MISTS IF TLV EXCEEDED
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN

[Search More](#)



ALL PAGES On Chemical Property IN THIS GROUP

NAME

- [ATOMIZED ALUMINUM POWDER, CODE:01-0840](#)
- [ATOMIZED ALUMINUM POWDER,ALCAN 201 OR X-85](#)
- [COMBAT, FIRE ANT KILLER](#)

CAS

- 7429-90-5
- 7429-90-5
- 67585-29-4

COMBAT, ROACH CONTROL SYSTEM	67585-29-4
COMBAT, ANT CONTROL SYSTEM	67585-29-4
SCM 4 0,SELECTRON LEAD-TIN STRIP SOLUTION	7647-01-0
	7732-18-5
FREON TF	76-13-1
ANSTAC M	
31-60059-206 POS ONE RINSE ADDATIVE	7631-90-5
	497-19-8
	7732-18-5
HYDROGEN PEROXIDE TOPICAL SOLUTION,P/N 5232	7722-84-1
	7732-18-5
POTASSIUM HYDROXIDE, 45% SOLUTION	1310-58-3
	7732-18-5
2X726-A DEGREASING SOLVENT	127-18-4
	71-55-6
	124-38-9
SOLITHANE(R) 113 RESIN	26471-62-5
C113-300	
CEE-BEE B-23	7664-38-2
	7664-39-3
CORTEC-369	106-97-8
PR-1538 BLACK,PART A	101-14-4
PR-1538 AMBER,BLACK,PART B	
MOLYKOTE 4X SPRAY	71-55-6
SOLDER	7439-92-1
	7440-31-5
DASCO GUARD 2336	
PHENYL PROPANOLAMINE HYDROCHLORIDE	154-41-6
FOSTA TUF-FLEX 730,IMPACT POLYSTYRENE	9003-55-8
CODE-ARC 7018M ELECTRODES-MIL-E-0022200/	7439-89-6
	13463-67-7
	7789-75-5
	7439-96-5
LEAD ACID BATTERIES	7439-92-1
	7664-93-9
FACTRAN EP-1	
FACTRAN EP-1;GREASE LUBRICANT	
ALLOY STEEL WELDING STUD	7439-89-6
	7439-96-5
	7440-47-3
	7440-02-0
STAINLESS STEEL WELDING STUD	7439-89-6
	7439-96-5
	7440-47-3
	7440-02-0
	7439-96-5
CERAMIC STUD WELDING FERRULE	14808-60-7
CARBON STEEL WELDING STUD	7439-89-6
	7439-96-5
WELDING STUD, ALUMINUM ALLOY	7429-90-5
	7440-21-3
	7439-95-4
	7440-47-3
SULFLEX SILICONE RESIN	
DPD FREE CHLORINE REAGENT	7558-79-4
	60-00-4
X7 XOMPOUND	75-09-2
	127-18-4
	108-95-2
	1310-58-3

HYDRO-SEAL,HVY DUTY COLD PART CLNR,HS-9,9K	1310-58-3 108-95-2 1319-77-3 127-18-4 75-09-2
HS-3 HYDROSEAL REPLENISHER	1319-77-3 127-18-4 108-95-2 1310-58-3 75-09-2
HYDRO-SEAL,HEAVY DUTY COLD PART CLNR,HS-3K	1310-58-3 108-95-2 1319-77-3 127-18-4 75-09-2
GOLIATH PEN OIL (AEROSOL	8030-30-6 71-55-6 628-63-7 74-98-6 75-28-5
W.I.ASBESTOS GASKET CLOTH-TACKY	12001-29-5 9006-04-6
FLEXIBLE POLYURETHANE FOAM	
P65 PALLADIUM CHLORIDE	7647-10-1
EUTEC SILVER WELD ECONOMIZER #2	7440-22-4 7440-50-8 7440-66-6 7440-31-5
UC100 SERIES REFRASIL	112945-52-5
CAS#7631-99-4, SODIUM NITRATE	7631-99-4
STICK-EM GLUE TRAPS	
8500 SPMC14 ACID CLEANER	105-55-5 7757-82-6 7681-38-1 25155-30-0
MAGNESIUM CHLORIDE	7786-30-3
349 STAINLESS	7440-02-0 7440-33-7 1309-37-1 7439-96-5 7440-47-3
BRAYCOTE MICRONIC 745	